

Cat. #1910

PELICAN™



1910

LEDSTRUCTION MANUAL

This compact flashlight produces an ultra bright light beam by using a LED powered by (1) one AAA 1.5V alkaline battery. The 1910 flashlight is designed for easy use with one hand operation and has a dual-switch mode for constant-on and momentary-on. The 1910 flashlight body is made by high precision CNC machines from aircraft-grade aluminum alloy for the most durable construction. The 1910 flashlight is water resistant.

TO INSERT BATTERY

1. Remove the tail cap by turning counter-clockwise.
2. Install (1) one AAA alkaline battery with + terminal facing to the head assembly.
3. Replace the tail cap onto the flashlight by turning clockwise until sealed.

OPERATION

High > Low > Off

1. MOMENTARY -

Gently depress the tail button for momentary operation.

Press once for high, press again (within a half second) to change from high to low.

2. CONSTANT ON -

- Single click for High
- Three clicks (no more than a half second between clicks) for low

3. LIGHT-OFF -

Press the tail button to turn OFF.

TO CHANGE BATTERY

1. Remove the tail cap by turning counter-clockwise until it comes off the rear of the 1910 flashlight.
2. Remove the (1) one used battery from the 1910 flashlight.
3. Install the (1) one new AAA alkaline battery with + terminal facing to the head assembly.
4. Replace the tail cap by turning clockwise until sealed.



1913-311-001 5-9157 Rev A
© 2013 Pelican Products NO/13

All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates.

GENERAL CARE AND MAINTENANCE

1. Clean o-rings with a soft clean cloth to insure that sealing area is free of dirt that could destroy the o-ring seal.
2. Apply a light coat of clear silicone grease on the o-rings occasionally if turning action becomes too difficult.
3. Remove the tail cap and wipe the rear threads of the 1910 flashlight body and inside of the tail cap with a soft clean cloth occasionally to avoid intermittent flashlight operation.

CAUTION

To prevent the 1910 flashlight coming on accidentally when the flashlight is stored, remove the batteries. If the 1910 flashlight is turned on while it is in a container, the flashlight can overheat and damage the flashlight or the material of the surrounding area.

SPECIFICATIONS

BULB: LED
Batteries: (1) One AAA alkaline or other equivalent alkaline battery

O-RING MAINTENANCE

Check closely for cuts, scratches, or otherwise damaged o-ring or mating lens lip surface. Remove any dirt or foreign matter from o-ring sealing surfaces. Keep threads, o-ring groove and inside lip of lens lubricated with silicone grease. See Warranty information for replacement of o-ring.

Battery Safety Information

WARNING: HANDLE AND STORE BATTERIES PROPERLY TO AVOID INJURY OR DAMAGE BATTERIES CAN BE DANGEROUS!

Most battery issues arise from improper handling of batteries, and particularly from the use of damaged or counterfeit batteries. Please review the information below to avoid serious injury and/or damage to your property.

Alkaline Batteries

1. For those lights with hazardous location safety approvals for explosive environments please be advised that the safety approval is only valid for the specified battery type manufacturer and, where applicable, brand names that are displayed on the flashlight and/or instructions sheets that are supplied with the light. The use of other battery technologies may reduce the performance of the flashlight and will invalidate the safety approval.
2. Always read the battery manufacturers recommendations for the appropriate use of the battery technology/brand prior to using the flashlight.
3. When replacing the batteries:
 - a. Replace all the batteries at the same time.
 - b. Do not mix battery brands and old and new batteries.
 - c. Always insert batteries correctly with regard to polarity (+ and -) marked on the battery and equipment.
4. Do not change batteries in a hazardous location.
5. Remove batteries from equipment if it is not to be used for an extended period of time.

Always dispose of all batteries properly at an approved battery recycling center.

