

## Model 210 Heated Recirculator



Model 210

### Key Specifications

Description	Heated Recirculator
Working Temperature Range °C	Ambient to 70°
Temperature Stability °C	±0.2°
Pump Type	Centrifugal

### Key Features

#### IMMERSION CIRCULATOR & OPEN TANKS

##### Key Features

- Large, universal icon and English display
- On-screen prompts
- Single-point calibration capability

### Common Specifications

Working Temperature Range °F	Ambient to 158°
Working Temperature Range °C	Ambient to 70°
Temperature Stability °F	±0.4°
Temperature Stability °C	±0.2°
Pump Type	Centrifugal
Pump Speed	Single

Process Connections	1/2" barb fitting
Over-Temperature Protection / Failsafe Heater Control	Yes
Low Liquid Level Protection	Yes
Maximum Ambient Temperature °F	95°
Maximum Ambient Temperature °C	35°
Overall Dimensions (L x W x H) (inches)	8 x 9.5 x 8 in
Overall Dimensions (L x W x H) (cm)	20.3 x 24.1 x 20.3 cm
Shipping Weight (pounds)	12.0
Shipping Weight (kilograms)	5.4
Catalog Page Number	67

### 60 Hz Only

Part Number	40300
Maximum Pressure (psi)	2.0
Maximum Pressure (bar)	0.13
Maximum Pressure Flow Rate (gpm)	3.00
Maximum Pressure Flow Rate (l/min)	11.4
Included Hardware	Tubing and clamps
Heater Wattage	750

### 50 Hz Only

Part Number	40301
Maximum Pressure (psi)	2.0
Maximum Pressure (bar)	0.13
Maximum Pressure Flow Rate (gpm)	3.00
Maximum Pressure Flow Rate (l/min)	11.4
Included Hardware	Tubing and clamps
Heater Wattage	750
Regulatory Approvals	CE