

Testo 316-3 Refrigerant Leak Detector

Rugged and Reliable

Testo 316-3 is a reliable refrigerant leak detector that delivers dependable, rugged performance at a great value. The proven heated diode sensor provides great sensitivity down to 0.15 ounces/year including the new refrigerant blends like R-410A, R-407C, and R-134a.

Just turn it on and start getting readings immediately! Thanks to the automatic zeroing, the testo 316-3 is extremely fast and can be used even in previously contaminated areas.



Features

- Designed for use on new refrigerants and blends
- Patented heated diode sensor provides excellent sensitivity
- High/low sensitivity adjustment
- Easy one button operation
- Automatic zeroing
- LED indicator and audible alarm
- Rugged housing

Testo 316-3 Refrigerant Leak Detector

testo 316-3, refrigerant leak detector

Includes: sensor head, transport case, calibration certificate, batteries and filter

Part no. 0563 3163



Technical data sensor

| | |
|-------------|--------------------|
| Sensitivity | 0.15 oz/yr; (4g/a) |
|-------------|--------------------|

General technical data

| | |
|-------------------------|---|
| Detectable refrigerants | R-22, R134a, R-404A, R-410A, R-507, R438A and all CFCs, HFCs, and HCFCs |
| Conformance | SAE J1627, EN 14624, EG 2004/108/EG |
| Operation temp. | -4 to 122 °F |
| Operation humidity | 20 to 80 %RH |
| Storage temp. | 32 to 122 °F |
| Battery type | 2 x D |
| Battery life | 16 hours continuous |
| Weight | 1 lb. |
| Warranty | 2 years |

Accessories

| | Part no. |
|--------------------------|-----------|
| 316-3 Replacement sensor | 0554 2610 |