Weller[®]

MG 130

Product no.: 130-1000-ESDN



Benefits

- > 100–240 power supply for global use
- > Filter alarm and 3 steps speed control
- > Small foot print design

The fume extraction unit MG 130 is easy to install and operate. Is supplied complete ready to place close to the workbench.

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com

Weller

	Technical Data	
(inches)International and the state of the st	Dimensions L x W x H (mm)	460 x 210 x 500
Voltage100 - 240 V, 50/60 HzPower100 WNoise level (distance 1 m) dB(A)< 52		18,11 x 8,26 x 19,68
Power100 WNoise level (distance 1 m) dB(A)< 52	Weight (approx.) in kg	11
Noise level (distance 1 m) < 52	Voltage	100 - 240 V, 50/60 Hz
dB(A) Max. vacuum Max. vacuum Capacity m³/h 140 Pre-filter Pre filter mat class F7 Compact filter Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Ch	Power	100 W
Capacity m³/h 140 Pre-filter Pre filter mat class F7 Compact filter Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Charles and the carbon + 50	Noise level (distance 1 m) dB(A)	< 52
Pre-filter Pre filter mat class F7 Compact filter Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Ch	Max. vacuum	
Compact filter Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Ch	Capacity m³/h	140
	Pre-filter	Pre filter mat class F7
Max. capacity 1–2 workstations	Compact filter	Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemi
	Max. capacity	1–2 workstations
RS232 interface (remote 1 x RS232 (TTL) control)	RS232 interface (remote control)	1 x RS232 (TTL)
USB port	USB port	
WX-compatible	WX-compatible	

Find Quality Products Online at:

www.GlobalTestSupply.com