

FD200 Flow-through Cooler

JULABO flow-through coolers are designed for applications below ambient temperature in combination with heating circulators. Advantages are low energy requirements and the avoidance of unnecessary cooling water consumption. Easy handling and a small footprint are additional positives.

JULABO flow-through coolers are an economic alternative to customary cooling with tap water. The devices are designed for use in an existing loop circuit, e.g. heating circulator with circulating pump.

Your advantages

- · For applications near ambient temperatures
- Integrated freezing protection
- · Low energy requirement
- · Preventing the use of precious tap water for cooling
- Compact design, small footprint
- Ease of operation



Technical data

| Available voltage versions | | | Cooling | |
|--------------------------------------|--|------------|---------------------------|--------------|
| Order No. | 9 655 825 | | Cooling of compressor | 1-stage Air |
| Available voltage versions: | | | | |
| 9 655 825.02 | 115V/60Hz (Nema N | 5-15 Plug) | | |
| 9 655 825.03 | 230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F) | | | |
| 9 655 825.05 | 230V/50Hz (CH Plug Type SEV 1011) | | | |
| Other | | | Dimensions and volumes | |
| IP Code | | IP 21 | Weight kg | 16 |
| | | | Dimensions cm (W × L × H) | 18 x 27 x 39 |
| Temperature values | | | | |
| Working temperature range °C +10 +30 | | | | |
| Ambient temperature °C 5 35 | | | | |

Performance values

115V/60Hz (Nema N5-15 Plug)

| 115 | //60H | z | | |
|------------------------------------|---------|-------------------------|-------|--|
| Coolir | ig capa | acity (Ethanol) | | |
| °C | 20 | 10 | | |
| kW | 0.22 | 0.18 | | |
| Refrigerant | | | R134a | |
| Filling volume g | | e g | 85 | |
| Global Warming Potential for R134a | | ing Potential for R134a | 1430 | |
| Carbon dioxide equivalent t | | de equivalent t | 0.122 | |

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com



230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

| 230 | //50H | Iz | | |
|------------------------------------|-------|-------|-------|--|
| Cooling capacity (Ethanol) | | | | |
| °C | 20 | 10 | | |
| kW | 0.22 | 0.18 | | |
| Refrigerant | | | R134a | |
| Filling volume g | | 85 | | |
| Global Warming Potential for R134a | | 1430 | | |
| Carbon dioxide equivalent t | | 0.122 | | |

230V/50Hz (CH Plug Type SEV 1011)

| 230V/50Hz | | | | |
|------------------------------------|------|--------------------------|-------|--|
| Cooling capacity (Ethanol) | | | | |
| °C | 20 | 10 | | |
| kW | 0.22 | 0.18 | | |
| Refrigerant | | | R134a | |
| Filling volume g | | e g | 85 | |
| Global Warming Potential for R134a | | ning Potential for R134a | 1430 | |
| Carbon dioxide equivalent t | | de equivalent t | 0.122 | |

All Benefits



JULABO. Quality. Highest standards of quality for a long product life.



Green technology. Development consistently applied environmentally friendly materials and technologies.



Satisfied customers. 11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified

JULABO support.



Quick start. Individual JULABO consultation and comprehensive manuals at your disposal.



100% Checked. 100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.

Services 24/7.

Find Quality Products Online at:

www.GlobalTestSupply.com

² sales@GlobalTestSupply.com