
Traceable® pH/ORP Meter Kit





- Triple display shows pH or ORP measurement, temperature and time\date
- Ideal for wastewater, water quality and environmental applications
- Convenient kit includes everything you need to start testing batteries, user guide, carrying case, ISO Guide 34 CRM pH buffers and Traceable® Certificate

Features:

- Accuracy: ±0.02 pH
- 25 point memory storage with time/date stamp
- Water-resistant (IP67)
- Individually serialized, calibrated, and certified Traceable® to NIST

Electrode features:

- Polycarbonate body housing
- o 12mm diameter, 4.4"/111mm length
- Single-junction gelled Ag/AgCl reference (sealed) with ceramic pin/pellon junction
- Full range pH sensor, 0.095" Platinum disc ORP sensor, and integral thermistor

Traceable to NIST for accuracy

An individually-numbered Traceable® Certificate is provided which assures accuracy from an ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

Cat. No. 4277 Traceable® pH\ORP Meter Kit

Cat. No. 4278 Probe Extension Cable Cat. No. 4279 Replacement Probe

Cat. No. 4290 Traceable® One-Shot ™ pH Buffer Standards (CRM) 6-Pack Assortment

TRACEABLE® PRODUCTS

Product Specifications

pH Range: 0.00 to 14.00 pH

▶ pH Resolution: 0.01 pH▶ pH Accuracy: ±0.02 pH

► ORP Range: -1800 to 1800 mV

► ORP Resolution: 0.1mV <1000mV

(1mV ≥1000mV)

► ORP Accuracy: ±20 mV

► Temperature

Range: 0 to 60°C

(32 to 140°F) (selectable)

Resolution: 0.1°

(1° when >100°)

Accuracy: ±1°C

www.GlobalTestSupply.com

Traceable Conductivity and pH Buffer Standards



The most accurate pH Standards available anywhere

- 100% compatible with all makes and instruments and electrodes
- Select values manufactured to IUPAC (International Union of Pure and Applied Chemistry) formulation—
 features long term buffer stability and buffer resistance to temperature changes during pH meter calibration

Features:

- Only Certified Reference Material meets all test requirements for Federal, State, and local agencies
- Triple-layered proprietary packaging—aluminum foil, PET and low-density polyethylene bag—prevents contamination by permeable gases and provides 2-year shelf life
- Each 16 ounce bottle or six pack single-use 100ml container is supplied with an individual temperature compensation chart, traceability information, Traceable® Certificate

Traceable to NIST for accuracy

A2LA ISO/IEC 17025:2005 (1750.01) (Calibration Laboratory) and ISO 17034 (formerly ISO Guide 34) (Certified Reference Material Producer) provide highest achievable levels of product production, documentation, and accuracy. Additional accreditations include ISO 31 (content) and ISO 35 (statistical analysis). ISO 9001 ensures that world-class product standards for Materials are always met. To assure accuracy an individually serial-numbered Traceable® Certificate is supplied to indicate traceability to standards provided by NIST (National Institute of Standards and Technology) and/or a National Standards Laboratory.



Traceable® pH Buffer Standards Certified Reference Material	(CDM)	(CUI UB)

Size	Accuracy	Color	Cat. No.	pH Value
16 oz. bottle	25°C is ±0.010 pH	Red	4880	4.005
		Yellow	4881	7.000
		Blue	4882	10.012
100 ml One-Shot™ (6-pack)	25°C is ±0.010 pH	Red	4887	4.005
		Yellow	4888	7.000
		Blue	4889	10.012
One-Shot™ Assortment (6-pack)		Red/Yellow/Blue	4890	4.005 — 10.012

Traceable® pH Buffer Standards Certified Reference Material (CRM) (CLEAR)

Size	Accuracy	Cat. No.	pH Value
16 oz. bottle	25°C is ±0.010 pH	4280	4.005
		4281	7.000
		4286	7.416
		4282	10.012
100 ml One-Shot™ (6-pack)	25°C is ±0.010 pH	4287	4.005
		4288	7.000
		4285	7.416
		4289	10.012
One-Shot™ Assortment (6-pack)		4290	4.005 — 10.012