

# IFC202

## USB DATA LOGGER INTERFACE

For use with the Micro Series  
Data Loggers



### Features

- Compatible With:
  - MicroTemp
  - MicroRHTemp
  - EggTemp
  - EggTemp-RH
  - EGMS
- "Plug and Play" - No Driver Installation Required
- Blue, Green and Red LED Indicators
- Reduced noise with longer sensor leads

MadgeTech's IFC202 interface cable communicates between the Micro series data loggers and the MadgeTech software. Through this interface, loggers can be started, stopped or downloaded.

The IFC202 has been redesigned, and is now "plug and play". It can be directly connected to a computer without installing any drivers. The improved IFC202 can now operate at up to 500 Volts RMS relative to the computer's earth ground when attached.

The IFC202 is equipped with communication LEDs, that provide a quick indication of the device status. The blue light illuminates when the device is plugged in and successfully recognized by Windows. The red light flashes when data is sent, and the green light flashes when data is received.



## IFC202 SPECIFICATIONS\*

**Operating Environment:** -20°C to +50°C  
(-4°F to +122°F)

**Materials:** Polycarbonate Enclosure

**Dimensions:** Enclosure: 1.9" x 0.69" x 0.32  
(48.4mm x 17.5mm x 8.1mm)

**Dimensions:** Cable: 6' included  
May be used with any shielded mini plug stereo cable up to 100'

**LEDS:** Blue and Red/Green

Blue: Illuminates when the device is plugged in and successfully recognised by Windows.

**LED Functions:** Red: Flashes when data is sent.

Green: Flashes when data is received.

## ORDERING INFORMATION

MODEL	DESCRIPTION
IFC202	USB Data Logger Interface for the Micro Series Data Loggers

ASK ABOUT  
OUR OTHER  
DATA  
LOGGERS

Temperature  
Humidity  
Pressure  
pH  
Level  
Shock  
LCD Display  
Pulse/Event/State  
Current  
Voltage  
Wireless  
Intrinsically Safe  
Spectral Vibration  
Motion

REV 3 2013.12.11