

SPECIFICATIONS FOR ANTI-FATIGUE DOME MATS

Model No. SDL857

| Properties | Test Method | Value |
|--------------------------------------------|-----------------------|------------------|
| Tensile Strength/Mpa | ASTM D412 | 5.05 |
| Elongation @ Break % | ASTM D412 | 400 |
| Abrasion/mm ³ | DIN 53516 | 210 |
| Hardness (shore A) | ASTM D2240 | 55 +/-5 |
| Specific Gravity | ASTM D1298 | 1.39 +/- 0.05 |
| Tear Strength/Nmm ⁻¹ | ASTM D624 | 42.15 |
| Heat Resistance | ASTM D573 70h at 70°C | No visual damage |
| Compression Set | ASTM D395 (Method A) | 21% |
| Skid Resistance (Slip) | ASTM 303-83 | 37 BPN |
| Swelling Resistance (Weight increase %) | ASTM D471 | N/A |
| ASTM Oil | | 1.82 |
| Brake Oil | | N/A |
| Cooling Oil | | N/A |
| Transmission Oil | | N/A |
| Cutting Oil | N/A | |

Color: Black

Material: Natural Rubber

Material Thickness: 1/2"

Dimensions: 2' W x 3' L

Weight: 10.5 lbs.

