

Zero Smog 4V

Product no.: T0053660299N



Benefits

- › Equipped with HEPA H13 particle filter and Fine dust pre-filter F7
- › Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces
- › Electronic filter control with optical and acoustical filter alarm
- › Low noise emission levels for quiet workspace
- › max. blower capacity 230 m³/h
- › RS232 port, can be remotely controlled via remote control (optional accessory) or by a PC with RS232 connection
- › Efficiency test via USB port
- › 4 casters to allow easy movement of the unit
- › For connection to a WX / WT station a T0058768767 WT Hub is needed



Technical Data

Dimensions L x W x H (mm)	345 x 325 x 505
Dimensions L x W x H (inches)	13.58 x 12.79 x 19.88
Weight (approx.) in kg	19
Voltage	120 V
Power	275 VA
Noise level (distance 1 m) dB(A)	51
Max. vacuum	2700 Pa
Capacity m ³ /h	230
Pre-filter	Pre-filter F7
Compact filter	Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb)
Max. capacity	1-4 workstations
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port.
USB port	on
WX-compatible	on