8" CHART RECORDER

Model: TH8-10 TEMPERATURE & HUMIDTY



8" (203mm) chart recorders offer the largest resolution out of any chart recorders. All chart recorders feature a large 8" chart and user-selectable recording time-frames and ranges. These units are compatible with Dickson's Replaceable Sensors™, making calibrating your chart recorder easier than ever.

FEATURES:

- Display
- Audible Alarms
- Ambient Temperature and Humidity Replaceable Sensor™

REPLACEABLE SENSOR™ SPECIFICATIONS:

Humidity Accuracy ±2.0% RH from 5% to 95% RH

Temperature Accuracy $\pm 0.8^{\circ}$ F (\pm .44C) from 20°F to 122°F $\pm 1.8^{\circ}$ F ($\pm 1^{\circ}$ C) remaing range

Temperature Range 32°F to 120°F (0°C to 50°C)

| Alarm Type | Audio/Visual |
|---|---|
| Ambient Operating RH Conditions | 0-95% RH non-condensing |
| Ambient Operating Temperature Conditions | 32°F to 120°F (0°C to 50°C) |
| Battery Backup | (4) C Batteries |
| Battery Life | 1 Month (Avg) |
| Calibration Options | N100, N300, N400 |
| Channels | CH1: Temperature CH2: Humidity |
| Chart Rotation Speed | 24 Hour, 7 Day |
| Dimensions LxWxH | 9 3/8″x2 3/4″x10 1/8″ |
| Display Dimensions | 5 1/8" x 1" |
| Display Type | LCD |
| Enclosure | Rugged Black ABS Case, Polycarbonate Door, Aluminum Dial |
| IP Rating | IP20 |
| Included Accessories | AC Adapter, Red Pen, Blue Pen, (4) C Batteries, Quick Start Guide and Replaceable Sensor™ *Charts sold separately |
| Mounting Options | Free Standing or Wall Mount (With Keyhole) |
| Power Cord | 6 ft |
| Power Source | 120 to 240 VAC, 12 VDC (INTL fittings available); AC Adapter |
| Power Status Indicator | LED Indicator |
| Unit Weight | 2.45lbs without batteries |
| Warranty | 12-Month Limited |
| Replaceable | RS010 |

Your Proven Partner for Environmental Monitoring



Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com