

# Fluke TL175 TwistGuard<sup>™</sup> Test Leads Twist. Test.

#### **Technical Data**

#### TL175 TwistGuard™ Test Leads offer:

- Patented TwistGuard<sup>™</sup> extendable tip shroud that meets new electrical safety requirements to reduce tip exposure while providing the versatility needed for most measurements
- New WearGuard<sup>™</sup> lead wire wear indicator. Each test lead is covered by two layers of silicone insulation; inner contrasting color is exposed when the leads are nicked, scuffed, or otherwise damaged and in need of replacement
- Double insulated silicone leads. TL175 withstands high temperatures and remains flexible in cold temperatures
- Extra-heavy strain relief on both probe-end and plug-end, tested beyond 30,000 bends without failure
- Universal input plugs compatible with all instruments that accept standard 4 mm shrouded banana plugs
- Probes always show correct category rating for tip exposure being used
- TL175E also available. Includes removable 4 mm lantern tips for versatility
- Conforms to EN61010-031
- Ratings: CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A max., Pollution Degree 2
- Environmental ratings: -20 °C to 55 °C
  (-4 °F to 131 °F), altitude: 2000 m (6,562 ft)





## **TL175 TwistGuard™ Test Leads**



Reduce tip exposure for accurate placement



Extreme strain relief tested to withstand over 30,000 bends



Increase tip exposure for CAT II probing



Universal plugs compatible with all 4 mm shrouded inputs



Reduce tip exposure for CAT III testing



 $We ar Guar d^{\text{\tiny{TM}}} \ indicator \ shows \ insulation \ damage$ 

Fluke. Keeping your world up and running.®

©2010-2012 Fluke Corporation. Specifications subject to change without notice. Printed in U.S.A. 5/2012 3860288C\_EN

Modification of this document is not permitted without written permission from Fluke Corporation.

### **Ordering information**

Model

**TL175** TwistGuard™ Test Leads